

# optiset E workpoints

The optiset E telephones are a family of digital telephones in a modern attractive design for use on the HiPath DX, Realitis DX and iSDX. Ranging from a simple digital telephone to sophisticated featurephones, these telephones are positioned to satisfy a wide range of user needs.

A user-friendly series of options is presented to the user via the display and the three menu keys, enabling fast and easy access to the DX telephony features.

- Open listening (monitor)
- Adjustable ringer (volume/pitch)
- Adjustable handset receive/speaker volume

## Benefits

- Improved staff productivity
- Easy to use
- Comprehensive range of telephones
- Comprehensive range of add-ons
- 2 wire digital interface
- PC integration for data and Microsoft TAPI applications
- Stylish design

The following optiset E telephones are available:

### optiset E entry

Cost effective entry into digital telephony.

### optiset E basic

The basic version for voice and data communications.

### optiset E standard

The comprehensive range of features optimised for telephone communications.

### optiset E advance/ optiset E advance plus

The professional configuration for voice and data communications.

### optiset E conference/conference pro

Full duplex audio transmission for high quality conference calls.

### optiset E entry

Telephone with:

- 3 function keys each with an LED
- 2 audio control keys
- Adjustable ringer volume
- Adjustable handset receive volume

This is an entry-level digital telephone designed for general purpose use. The standard keypad is complemented by a message waiting LED with key, redial key and enquiry key.

### optiset E basic

Telephone with:

- 8 function keys each with an LED
- 2 audio control keys
- One adapter plug in position

This is a basic feature phone providing the user with keys pre-configured with the most commonly used DX telephony features and access to data functionality via an add-on adapter. The LED keys may also be programmed for use in a keysystem group.

### optiset E standard

Telephone with:

- 12 function keys each with an LED
- 2 audio control keys
- 3 menu keys
- Handsfree
- 2x24 character display
- Adjustable ringer (volume/pitch)
- Adjustable handset receive/speaker volume

This is a mid-range featurephone providing the user with the ability to personalise the functions of the keys with LEDs, via an interactive menu system, for increased productivity. The keys with LEDs may be used as keysystem keys, for manager/secretary working, for frequently dialled numbers or for DX features.

The display provides information such as caller's name or number, and is used to guide the user through the menu system.

### optiset E advance

Telephone with:

- 12 function keys each with an LED
- 2 audio control keys
- 3 menu keys
- 2 adapter plug in positions
- Up to 2 add-on key modules
- Open listening (monitor)
- 2x24 character display
- Adjustable ringer (volume/pitch)
- Adjustable handset receive/speaker volume

This is a high-range featurephone providing all the functions of the optiset E standard plus the ability to support two add-on units.



HiPath DX

**SIEMENS**

Global network of innovation



## Adapters

The optiset E adapters are fully encapsulated, slide-in modules which can be installed and removed easily at the back and on the underside of the optiset E telephones. In this way the telephones can be adapted quickly and easily to specific workplace and organisational changes.

### optiset E phone adapter

The optiset E phone adapter enables an additional optiset E telephone to be connected to the system without the need for additional cabling. The telephones can be reached simultaneously via independent numbers.

### optiset E data adapter

The optiset E data adapter enables asynchronous V.24 terminals to be connected at data rates up to 56kbits.

### optiset E ISDN adapter

The optiset E ISDN adapter enables standard basic rate ISDN terminals (e.g. PC with ISDN SO card or video device) to be connected.

### optiset E contact adapter

The optiset E contact adapter has 2 connectors for accessing external busy lamps and second bells. There are two separate outputs:

- The first output provides the active telephone status (e.g. handset offhook, headset activated)
- The second output provides the ringing sequence

### optiset E analogue adapter

The optiset E analogue adapter allows the connection of an additional analogue terminal (e.g. group 3 fax machine, PC with modem card, cordless telephone).

### optiset E acoustic adapter for analogue telephone accessories (only available for optiset E advance plus)

The optiset E acoustic adapter is used to connect analogue telephone accessories (e.g. external loudspeaker, microphone or second earphone).

### optiset E headset adapter optiset E headset adapter plus

The optiset E headset adapter permits the connection of two headsets. The use of a headset offers numerous advantages, especially for users with high call rates (e.g. call centres, attendant consoles or sales/telemarketing departments).

The second headset can be used by another person in the room (e.g. during an important call or ACD training). In addition to the features of the optiset E headset adapter, the optiset E headset adapter plus offers a connection for a recording device, enabling the user to register and document important calls.

### Control adapter

Provides a data and headset connection for use with CTI applications.

### optiset E PNT-E ISDN adapter

The ISDN adapter box PNT-E (Private Network Termination Evolution) enables remote data terminals, PC's, video equipment, group 4 fax machines and ISDN telephones to be connected at competitively low cost.

### Dummy panel

If no adapters are used the plug in positions may be covered with a dummy panel.

### Accessories

The following accessories may be added to the optiset E telephones to enhance their performance and to tailor them for personal use.

### Headsets

The headset replaces the telephone handset thus leaving both hands free when making a call. This is particularly important for users with high calling rates. The following headsets can be connected to the optiset E headset and headset plus adapters:

- Profile binaural I Encore
- Profile I Encore binaural
- Profile 3 in 1 I Tristar
- optima I Supra
- optima duo
- ADDvantage plus
- ADDvantage duo

### Add-on microphone

The add-on microphone replaces the microphone integrated in the telephone. It helps make optimum use of 'handsfree talking' even under difficult acoustic conditions and allows greater freedom of movement while telephoning. Technical data dimensions (HxBxD) in mm: 25x68x77. Colour: warm grey.

### Active loudspeaker box

The additional active loudspeaker box can be used instead of the loudspeaker integrated in the telephone and offers improved sound quality during 'hands free talking'. The volume can be set using the volume control button. Technical data: dimensions (HxBxD) in mm 160x98x95. Colour: warm grey.

### optiset E advance plus

Same features as optiset E advance, plus

- Handsfree

### optiset E conference

As for the advance plus but also includes:

- Full duplex, echo suppression and acoustic room adaption for conference calls

### optiset E conference pro

As for the conference but also includes:

- Acoustic adapter
- Speaker
- Microphone

For large conference rooms where participants need to sit at both ends of the table.

### optiset E key module

The optiset E key module is an add-on device with 16 keys each with an LED. It may be connected to the optiset E advance, advance plus, conference and conference pro. A maximum of 2 key modules may be attached to 1 telephone.

### optiset E privacy module

The optiset E privacy module provides protection against telephone tapping. Also suitable for use on numerous digital and analogue handsets.

## Second earphone

The second earpiece can be used to eliminate disturbances due to ambient noise, or to enable a second person to listen in.

## Press-to-talk handset

This handset can be plugged into any of the optiset E telephones in place of the normal handset.

## Press-to-mute handset

This handset can be plugged into any of the optiset E telephones in place of the normal handset.

## ACD working

An alternative key layout for ACD working on optiset E standard, advance and advance plus is supported by pre-printed labels.

## Uni Client and TAPI

The Uni Client application can be used on an adjacent PC, with the optiset E basic, advance, advance plus, conference and conference pro to provide point & click access to DX features, directories and voice mail. (Requires optiset E data adapter).

## Technical data

### Connection system

Telephone side:  
Mini-Western connector (RJ14).  
Network side:  
Mini-Western connector (RJ14).

### System interface

- 2 channel digital interface UPO/E
- 2 wire connection

### Operational ranges

- With 16 dB attenuation at least 1200 metres with 0.6 PVC cable
- With CAT3 cable at least 1200 metres
- With CAT5 cable at least 1200 metres
- With CW1308 cable at least 1200 metres
- Master/slave (second telephone connected via phone adapter) maximum 100m

### Connection cord

- 3m (standard)
- Colour: warm grey or anthracite (black)

### Wall holder

- Narrow wall holder for optiset E entry and optiset E basic
- Wide wall holder for optiset E standard, optiset E advance, optiset E advance plus, conference and conference pro
- Telephones with the add-on optiset E key module cannot be mounted on a wall holder

## Power supply

Plug-in power supply unit for complex telephone configurations (telephones with adapters, add-on devices).

## optiset E headset adapter

Two integrated RJ11 sockets.

## optiset E headset plus adapter

Same as optiset headset adapter, but featuring additionally: one RJ12 socket for 600 Ohm recorders for the connection of analogue/digital recorders.

## Overview of features

Telephone/optiset E	Entry	Basic	Standard	Advance	Advance Plus	Conference	Conference Pro
Feature keys with lamp	3	8	12	12	12	12	12
Dial keypad	•	•	•	•	•	•	•
2 audio control keys	•	•	•	•	•	•	•
Open listening			•	•	•	•	•
Adapter plug-in position	0	1	0	2	2	2	2
Handsfree talking			•		•	•	•
3 menu keys			•	•	•	•	•
Display (symbol)			2x24	2x24	2x24	2x24	2x24
Message waiting key and lamp	•	•	•	•	•	•	•
ACD working				•	•	•	•
Autoanswer			•	•	•	•	•
Connection facility for optiset E key module (maximum 2)				•	•	•	•
Wall installation	•	•	•	•	•	•	•
Hearing aid compatible	•	•	•	•	•	•	•
Full duplex hands free						•	•
External speaker and microphone							•



## Dimensions and weights

Type	Weight (mm)	Width (mm)	Depth (mm)	Height (mm)*
optiset E entry	706	151	253	74/106
optiset E basic	725	151	253	74/106
optiset E standard	974	216	253	74/106
optiset E advance	965	216	253	74/106
optiset E advance plus	971	216	253	74/106
Conference	971	216	253	74/106
Conference pro	971	216	253	74/106
optiset E key module	391	137	253	74
Privacy module	300	92	200	39
optiset E phone adapter	118	76	165	48
optiset E data adapter	160	76	165	48
optiset E ISDN adapter	132	76	165	48
optiset E contact adapter	132	76	165	48
optiset E analogue adapter	150	76	165	48
optiset E acoustic adapter	119	76	165	48
optiset E headset adapter	122	76	165	48
optiset E headset plus adapter	120	76	165	48
Wall holder wide/narrow	167	160/95	182/182	77/77
Control adapter	132	76	165	48
PNT-E adapter	250	105	35	70
Plug-in power supply	500	48	64	79

\*Height with/without handset

### About Siemens Enterprise Communications Limited:

Siemens Enterprise Communications is one of the world's leading vendors of Open Communications solutions for enterprises of all sizes, enabling business processes to be more productive, faster and more secure – with any device, network or information technology infrastructure. The company is a wholly owned subsidiary of Siemens AG with 17,000 employees globally and headquarters in Munich.

Visit the website at [www.siemens.com/enterprise](http://www.siemens.com/enterprise) or for UK specific information at [www.siemens.co.uk/enterprise](http://www.siemens.co.uk/enterprise)

Siemens Enterprise Communications Limited  
Brickhill Street, Willen Lake, Milton Keynes. MK15 0DJ  
Tel. 01908 855000 • Fax. 01908 855001

• Publication no. 1QHA 50532 AAA-CAA

• Issue 04

[www.siemens.co.uk/hipathdx](http://www.siemens.co.uk/hipathdx)

Freephone 0800 512412



FS 261



The information provided in this document contains merely general descriptions or characteristics of performance which in case of actual use do not always apply as described or which may change as a result of further development of the products. An obligation to provide the respective characteristics shall only exist if expressly agreed in the terms of contract. Availability and technical specifications are subject to change without notice. © Siemens Enterprise Communications Limited 2006. All rights reserved. Siemens and HiPath are registered trademarks of Siemens AG. HiPath DX is a trademark of Siemens AG. Realitis, Realitis DX and iSDX are registered trademarks of Siemens Enterprise Communications Limited. All other trademark product and company names are the property of their respective owners.